



Patent nos. D583,461; D585,972; D588,537

## 12"/30cm | UB30 High Volume Blower/Exhauster

- Dual voltage/dual frequency/one unit
- High impact polyethylene shell
- Glass-filled nylon turbo fan blade
- Low starting amps
- IP55 rain tested switch enclosure
- Stackable design feature
- Comes with standard 15'/4.6m power cord
- Compatible with UB20 M.E.D™ System
- IMPA Codes:  
EJ4002 - 591403  
EJ8002 - 591407

Optional Accessories: Standard Duct, Duct Storage Bag, Duct Reducer/ Adapter



MODEL	UB30	UB30
<b>Order #</b>	<b>EJ4002</b>	<b>EJ8002</b>
<b>STOCK LOCATIONS</b>		
<b>FREE AIR</b>	2,420cfm/4,114m <sup>3</sup> /hr	2,017cfm/3,429m <sup>3</sup> /hr
<b>15ft/4.6m Duct</b>		
Straight	2,250cfm	2,805m <sup>3</sup> /hr
1-90° turn	2,050cfm	2,550m <sup>3</sup> /hr
2-90° turns	1,875cfm	2,340m <sup>3</sup> /hr
<b>25ft/7.6m Duct</b>		
Straight	1,950cfm	2,465m <sup>3</sup> /hr
1-90° turn	1,825cfm	2,380m <sup>3</sup> /hr
2-90° turns	1,750cfm	2,250m <sup>3</sup> /hr
<b>IMPELLER</b>	11-blade	11-blade
<b>DUCT ADAPTER(S)</b>	2	2
<b>WEIGHT</b>	37lbs/17kg	37lbs/17kg
<b>DIMENSIONS (h/w/d)</b>	20/15.5/12 in 508/394/305 mm	20/15.5/12 in 508/394/305 mm
<b>NOISE</b>	95dB	95dB
<b>MOTOR</b>	1Hp	0.8kW
<b>ELECTRIC</b>	115V, 1ϕ, 50/60Hz	240V, 1ϕ, 50/60Hz
<b>AMPS – RUN/START</b>	8A/33A	5A/17A
<b>APPROVALS</b>		

